



Solutions Portfolio

Complete Quality Management

2025



SUN NUCLEAR
A MIRION MEDICAL COMPANY

Better Quality Management. Better Care.

Sun Nuclear provides the
broadest range of advanced
Patient Safety solutions.



SunSCAN™ 3D
Next-Generation Cylindrical
Water Scanning System
See pgs. 36-38 for details.

Sun Nuclear Overview	4
Independence	6
SunServices™	8
SunCHECK® Platform	
Platform Overview	10
SunCHECK® Patient	12
PlanCHECK™	13
DoseCHECK™	13
PerFRACTION™	14
AdaptCHECK™	14
SunCHECK® Machine	16
SNC Machine™	17
SunCHECK® Machine Phantoms	18
SunCHECK® Device Integration	19


Patient QA Solutions	
ArcCHECK®	21
MultiPlug™	21
CavityPlug™	21
MapCHECK® 3	22
Gateway™	22
Plan AI™	23
IVD™ 2 / rf-IVD™ 2	23
SRS MapCHECK®	24
AVa™ Phantom	24
<i>See also StereoPHAN™ (pg. 27) and MultiMet-WL Cube (pg. 27).</i>	

Machine QA Solutions	
StereoPHAN™	27
MultiMet-WL Cube	27
STEEV™ Phantom	28
SRS MR Distortion Phantom	28
IC PROFILER™	29
Quad Wedge Plates	29
Daily QA™ 3	30
Solid Water® HE	30
Dynamic Thorax Phantom	32
XSight® Lung Tracking System Kit	32
Enhanced Dynamic Platform	32
TomoDose™	33
Daily ISO™ Phantom	33
RapidCHECK™	34
Advanced Electron Density Phantom	34

Dosimetry Solutions	
SunSCAN™ 3D	37
SunDOSE™ Software	38
Mini-Lift Table	38
Reservoir	38
SunSCAN™ TPR	38
SunSILICON™ & SunSILICON™ P Detectors	39
ATOM® Phantom Family	39
1D SCANNER™	40
PC Electrometer™	40
Reference Detector	41
EDGE Detector™	41
SNC125c™	41
SNC350p™	42
SNC600c™	42

Diagnostic QA Solutions	
Doppler Ultrasound Phantoms	45
B-Mode Ultrasound Phantoms	45
CT ACR 464 Phantom	46
IQphan™	46
RapidCHECK™	46
Multi-Energy CT Phantom	47
Mercury 4.0 Phantom	47
CTDI Phantoms	48
CT Perfusion Phantom	48
AAPM CT Performance Phantom	48
Stereotactic Needle Biopsy Phantom	49
Multi-Modality Breast Biopsy and Sonographic Trainer	49

Image Guided Abdominal Biopsy Phantom	49
DBT QC Phantom	50
Mammo FFDM™ Phantom	50
Mammo CESM™ Phantom	50
Mammo 156™ & 156D Stereo™ Phantoms	51
Mammo 3D Performance Kit	51
Supporting Solutions from the Mirion Portfolio	
Instadose®VUE	53
evrCAM™	53
IC3™ Survey Meter	54
RDS-Med™ Area Monitor	54
DMC 3000™ Dosimeter	55
ConnectStudio™ Software	55



Trusted.

Hospitals & clinics worldwide choose Sun Nuclear.

Linac manufacturers, imaging manufacturers, researchers, and scientific associations leverage Sun Nuclear solutions routinely, too. Collectively, the fields of Radiation Therapy and Diagnostic Imaging count on us to help:

- **Mitigate errors**
- **Reduce inefficiencies**
- **Validate technologies and techniques**
- **Elevate clinical care**

Through 40 years of service, we have come to know Quality Management from all angles — and we're proud of the unique role we play in protecting Patient Safety.

Today, Sun Nuclear is stronger than ever as the cornerstone of Mirion Medical, a growing division within Mirion.

Mirion Medical innovations power the fields of Radiation Therapy QA, Diagnostic Imaging QA, Occupational Dosimetry, Nuclear Medicine and Medical Imaging Tables and Accessories. Comprised of brands and product lines including Sun Nuclear, ec² Software, Dosimetry Services, Capintec and Biodex, the Mirion Medical group is dedicated to offering healthcare practitioners and patients a safer, more efficient healthcare experience -- in pursuit of The Science of Better.

Learn more: mirion.com/medical

40

Years Serving the Radiation Oncology and Diagnostic Imaging Fields

130+

Countries with Sun Nuclear Solutions

6,000+

Worldwide Cancer Treatment Facilities Use Sun Nuclear Solutions

>90%

of U.S. Cancer Treatment Centers Use Sun Nuclear Solutions

20+

Countries with SunServices™ Team Member Representation



Independence.

It's the essence of everything we do.



Unrelenting

for safer, more effective treatments.

Independent Quality Management empowers clinical physicists to be guardians of Patient Safety, and to efficiently fulfill complex safety requirements.

Unbiased

for truth in data and analysis.

Independent Quality Management — free from the bias of self-checking — drives accurate, standardized data analysis and redundancies essential to reducing risk.

Unencumbered

to stay focused on catching errors.

In an expanding universe of imaging and treatment variables, independent Quality Management detects and prevents clinically relevant errors — ensuring safety is never taken for granted.

“A critical aspect of a QA program is independence; that is, the QA procedures conducted to assure the quality and accuracy of the product or process must be independent of the product or process itself.”

G.S. Ibbott, Journal of Physics: Conference Series 250 012001 (2010)

SunServices™

We deliver expert support for independent Quality Management.

Through our SunServices team, Sun Nuclear provides protection for your investments in Patient Safety and your clinical program.

With deep experience across the continuum of Quality Management, we know the world in which you work – and deliver the responsiveness your department demands.



100 Support Team Members in 20+ Countries



Professional Services to Ease Technology Adoption




Onsite or Online World-Class Training



Industry-Leading Service Expertise



Our Melbourne, Florida-based 5,000 sq. ft. Training Center features a fully-functional linac bunker, lab-style classroom and large lecture hall.




10-point Quality Service repair for Sun Nuclear solutions are available at strategically-located SunServices Centers.

SunCHECK® Platform

Powering Quality Management in Radiation Therapy

1,500+
Unique Cancer
Treatment Centers
Globally



Scalable to meet the needs of any clinic or network, SunCHECK helps reduce risks, control costs, and improve treatment quality.



Platform

- One Solution for Quality Management
- Consistent and Efficient Workflows
- Seamless Clinical Integration
- Access from Anywhere



Patient

- Plan Quality Assessment
- Plan Checks
- Secondary Dose Calculations
- Pre-Treatment QA
- In-vivo Monitoring



Machine

- Daily, Monthly, Annual QA
- Measurement Device Connectivity
- Imaging, VMAT, MLC QA
- Time-savings on Routine Tasks

Implementation Made Easy

The SunCHECK Platform can be implemented via an on-premise server or **Cloud-hosted SaaS option***, based on your unique setup and maintenance requirements. The SaaS model is **ISO/IEC 27001:2013 certified** — assuring Radiation Therapy departments and their IT teams that SunCHECK is a robust and secure solution, with built-in backup and data redundancy.

SunDEPLOYS™ implementation services ensure your team achieves true workflow enhancements, and your staff is confident in bringing SunCHECK into routine use.

* Ask your Sun Nuclear representative or distributor about availability.

SunCHECK® Patient

Independent Patient QA
in a Single Workflow

Purposefully Automated, yet Customizable


- Streamlines data transfer and time-consuming Patient QA tasks
- Flexible, automated analysis options, compatible with your planning and delivery technologies

Common, Browser-Based Analysis Software

- One database across all Patient QA phases
- Ability to support Single Sign-On (SSO)/Active Directory
- Worklist-oriented dashboard
 - Overview of Patient (and Machine) QA status
 - Quick access to results, reviews, to-do's, and approvals
 - Verify successful completion of QA
- On-premise server or Cloud-hosted SaaS implementation options

Efficient, Independent Patient QA Oversight

- Review and approve Patient QA and plans
- Physician review of results, with QA information on anatomy
- Consistent, interactive event display shows point dose, 2D analysis, 3D analysis, structure-based gammas, overall gammas, DVHs, and images and dose displays



Specifications

Browser Support	Google Chrome (Recommended), IE11
Meets Reimbursement/Reporting Requirements	Yes
Supported Treatment Modalities	3D CRT, IMRT, VMAT, SRS and SBRT
Certification	ISO/IEC 27001:2013 for information security management, including SaaS deployment of SunCHECK

PlanCHECK™

Plan Quality Assessment
& Plan Checks

Automated Treatment Plan Validation

- Assess plan feasibility and complexity for insights on meeting clinical goals and patient plan deliverability
- Assess performance versus intent
- Automate time-consuming tasks to ease burden on medical physics staff

Software Highlights

- Automatically loads data from Varian Medical Systems® Eclipse™ and other DICOM-compliant TPSs
- Dosimetric checks compare dose/volume metrics to user-defined constraints
- Physics Checks verify treatment and non-treatment beams, and validate image and contour data

Specifications

Treatment Planning Systems Supported	Varian Medical Systems® Eclipse™ via Scripting, others via DICOM
Physics Checks	Rules-based checks: Treatment and non-treatment beam verifications, plan parameters, structures and deliverability
Dosimetric Checks	Structure-based checks: Dose/volume metrics with user-definable constraints; complex dosimetry metrics such as Conformality Index, Conformation Number, Gradient Index and Gradient Measure for multiple structures, plus Homogeneity Index, Inhomogeneity Index and more

DoseCHECK™

Secondary Checks

Automated, Independent 3D Secondary Dose Calculations

- Treatment plan support for 3D, IMRT, VMAT, SRS, SBRT, Varian Medical Systems® Halcyon™ System, Accuray's TomoTherapy® and Radixact Systems, and HDR Brachytherapy
- Efficiently investigate point doses, calculated vs. planned MUs, and 3D dose displays
- Launch directly from Varian Medical Systems® Eclipse™ treatment planning system

Specifications

Supported Systems	• Elekta and Varian Medical Systems® Linacs, including Varian Medical Systems® Halcyon™ System • Accuray TomoTherapy Hi-Art®, H-Series™, Radixact® Systems, and CyberKnife® System, including Precision Treatment Planning System • Varian Medical Systems® and Elekta HDR Brachytherapy Systems
Dose Calculation Algorithms	• Conventional Linacs - Collapsed Cone Convolution Superposition, optional Monte Carlo • TomoTherapy Systems - Monte Carlo • HDR Brachytherapy TG-43 compliant algorithm
Available Analysis & Pass/Fail Criteria	• Photon Composite & Beam Point doses, MUs*, 3D Dosimetric Analysis • Electron Beam Point doses • HDR Composite Point doses, Source Information, 3D Dosimetric Analysis

**Varian Medical Systems® and Elekta linac plans only.*



“Our Physicians regularly ask us to ‘SunCHECK’ a patient when they see something they’d like to investigate. The automated, immediate feedback on patient delivery improves our workflow...”

Mark Young, Ph.D.,
Chief Physicist, Providence Queen of the Valley Medical Center, U.S.

NOW AVAILABLE
SciMoCa™ for Elekta Unity systems,
providing online adaptive secondary
dose calculations

Varian Medical Systems® is a registered trademark, and Eclipse™ is a trademark, of Varian Medical Systems, Inc. Sun Nuclear Corporation is not affiliated with or sponsored by Varian Medical Systems, Inc.

PerFRACTION®

Phantomless & Array-Based
Pre-Treatment QA

In-Vivo Monitoring

Flexible Pre-Treatment QA Analysis

- 3D measurement analysis using EPID and/or Log File data*
- Independent Absolute Dose Analysis using EPID*

ArcCHECK® Direct Device Integration

- Direct device connectivity to **ArcCHECK** array for enhanced root-cause analysis of delivery issues

Compliance

- Meets AAPM Task Group 218 requirements for pre-treatment QA**

Specifications

Data Sources	EPID and/or Log Files (dependent on Linac and imaging type used in delivery), and/or ArcCHECK array
Available Analysis & Pass/Fail Criteria	• Composite and Beam Point Doses, 2D Relative Dose Analysis, 3D Dosimetric Analysis • 2D Absolute Dose Analysis (Transit Dosimetry Option*)

* PerFRACTION Dosimetry
** For Varian Medical Systems® non-SRS/SBRT and FFF plans

Automatically Track & Verify Dose

- Validate patient setup against the treatment plan
- Verify first fraction dose delivery vs. plan
- Review ongoing fractions

Catch & Document Common Errors

- Anatomy issues
- Setup-related issues

Result Analysis Options

- 3D using EPID and/or Log File data, or
- 2D through the Transit Dosimetry* feature

Specifications

Data Sources	EPID and/or Log Files (dependent on Linac and imaging type used in delivery)
Dose Calculation Image Set	Planning CT, Cone Beam CT
Available Analysis & Pass/Fail Criteria	• Composite and Beam Point Doses, 2D Relative Dose Analysis, 3D Dosimetric Analysis • 2D Absolute Dose Analysis (Transit Dosimetry Option*)

AdaptCHECK™ NEW

Online Adaptive Patient-Specific QA


For Varian Medical Systems® Ethos™ Therapy

- Built upon the proven SunCHECK® Patient Workflow
- Secondary dose calculations for pre-treatment QA
- Plan-of-the-day calculations to inform real-time adjustments per current patient anatomy
- Quick plan re-calculations to keep treatments safe, effective and on track

Specifications

Dose Calculation Algorithm	Collapsed Cone Convolution Superposition
Data Sources	Log Files
Dose Calculation Image Set	Planning CT, Cone Beam CT
Available Analysis & Pass/Fail Criteria	3D Dosimetric Analysis (universal or custom metrics), DVH, Gamma

Varian Medical Systems® is a registered trademark of Varian Medical Systems, Inc. Sun Nuclear Corporation is not affiliated with or sponsored by Varian Medical Systems, Inc.



“With PerFRACTION, we’ve shown that **large-scale clinical implementation of in vivo transit dosimetry is feasible**, even for complex techniques.”

Evy Bossuyt, M.Sc.,
Iridium Network

An Evolving In-Vivo Program

In the first two years of one network’s in-vivo dosimetry program, errors were detected in 7% of fractions analyzed. The data drove immediate corrective actions and new departmental protocols.*

Now, from insights uncovered over four years of their in-vivo program with SunCHECK, they have developed a process to address failed treatment fractions — leading to year-over-year decreases in failed fractions.


*Published findings: Evaluation of automated pre-treatment and transit in-vivo dosimetry in radiotherapy using empirically determined parameters, E. Bossuyt, et al, Physics and Imaging in Radiation Oncology 16 (2020) 113–129.

Learn more about this department’s experience here >



SunCHECK® Machine

Complete Machine QA in One Streamlined Application



Standardize Daily, Monthly, Annual QA

- Standardize shared tolerances among clinics, machines and staff
- Leverage ready-to-use, and customizable, QA templates

Common, Browser-Based Analysis Software

- One database for all Machine QA
- Quickly review completed QA and drill-down into results
- Task scheduling offers quick insight on tasks coming due or overdue
- On-premise server or Cloud-hosted SaaS implementation options

Automated Data Collection and Imaging

- **Daily QA™ 3, IC PROFILER™** and **IC PROFILER™-MR** direct device connectivity automates data collection
- Automatic capture of QA beam delivery captures, processes and analyzes images or log files

Easily Meet Compliance

- Complete AAPM Task-Group 142 tasks, with pre-set templates
- Meet DIN and other daily, monthly and annual QA protocols

Specifications

Browser Support	Google Chrome (recommended), IE11
Meets Reimbursement/Reporting Requirements	Yes
Certification	ISO/IEC 27001:2013 for information security management, including SaaS deployment of SunCHECK

SunCHECK® Machine

Daily, Monthly, Annual QA

Standardized, Efficient Machine QA

- Share tolerances among clinics, machines and staff
- Gain efficiencies with ready-to-use, but customizable, templates
- Complete all TG-142 and DIN QA easily within SunCHECK Platform
- Asset management for linking departmental equipment to tasks
- External data import, for single source storage and reporting, including Varian Medical Systems® Machine Performance Check

Automated Data Capture

- Automate beam measurement with direct integration to **Daily QA™ 3, IC PROFILER™, PC Electrometer™, 1D SCANNER™** and **IC PROFILER™-MR** devices.
- Eliminate additional software needed for data transfer

Specifications

Protocol support	• TG-142 (all 127 tests in tables 1-6) • TG-51 • DIN • Daily QA Support TG-66, TG-148, TG-135 and 10CFR 35 • Custom templates
Direct Device Connection	1D SCANNER, Daily QA 3, PC Electrometer, IC PROFILER and Quad Wedges (Optional) and IC PROFILER-MR devices

SNC Machine™

Imaging, VMAT, MLC QA

Automated QA Beam Capture

- SunCHECK Machine automatically captures, processes and analyzes images or log files
- Results are stored within SunCHECK Machine for easy review/audit
- Notifications may be turned on for pass/fail status

Imaging Phantom Support

- Supports most QA/QC Phantoms, including CT ACR 464 Phantom, Mobius MC2 Phantom MV/kV QA, and CBCT QA Phantom with QUART DVT_VN
- Works with Sun Nuclear **MV-QA, kV-QA, FS-QA, and WL-QA Phantoms** (see next page for details)
- ‘No Phantom’ analysis also available

Specifications

Imaging Test Support	• Image Quality CBCT, kV, MV • MLC • VMAT
MLC/ Mechanical	• MLC Picket Fence, Positioning, Leaf Speed, Transmission, Hancock • Winston Lutz Radiation & Machine Isocenter, Hancock • Starshot Gantry, Couch, Collimator • Light/Radiation Field Congruence • 4-Quadrant Jaw QA
VMAT	• Dose Rate vs. Gantry Speed • Leaf Speed • Arc Point Dose • DMLC Point Dose




“Our IT group was overjoyed that we could uninstall 5 or 6 software applications and instead have only a web-based application they needed to support. They have been able to take a reduced, hands-off approach to managing the system.”

Mark Geurts, M.S., Chief Physicist, Aspirus Health System, U.S.

Varian Medical Systems® is a registered trademark of Varian Medical Systems, Inc. Sun Nuclear Corporation is not affiliated with or sponsored by Varian Medical Systems, Inc.

SunCHECK® Machine Phantoms

MV-QA



Applications

- Image scaling, positioning offset, spatial resolution, contrast, uniformity and noise
- Easy setup, alignment clearly marked on overlay and image

MV Line Pairs (mm)	0.1, 0.2, 0.5, 1.0 ± 0.025
MV ROI	9 (4 spatial, 4 contrast, 1 center)
MV Dimensions (cm)	12.7 L x 10.2 W x 2.5 D

kV-QA




Applications

- Image scaling, positioning offset, spatial resolution, contrast, uniformity and noise
- Easy setup, alignment clearly marked on overlay and image

kV Line Pairs (mm)	0.6, 1.2, 1.8, 2.4 ± 0.01
kV ROI	28 (4 spatial, 23 contrast, 1 center)
kV Dimensions (cm)	12.7 L x 12.7 W x 1.6 D

FS-QA




Applications

- Symmetric and asymmetric light field/radiation field coincidence and jaw positioning
- Flatness and symmetry for photon and electron beam profile constancy

Field Sizes (cm)	10 x 10; 15 x 15
Markers (±0.1 mm)	56 - Field size (7 per field edge)
Dimensions (cm)	17.8 L x 17.8 W x 0.6 D

WL-QA



Applications

- Winston-Lutz measurements
- Imaging and radiation field isocenter coincidence
- Cone-beam CT positioning/repositioning
- End-to-end IGRT positioning tests
- 3D isocenter offset results

Dimensions (cm)	6.0 x 6.0 x 6.0
Sphere Size (mm)	7.0
Sphere Center Accuracy (mm)	0.2

SunCHECK Device Integration

Connectivity & Control

The SunCHECK Platform allows full control of essential Sun Nuclear Patient and Machine QA devices, without having to launch or maintain a separate application. Automated data collection and beam measurements help streamline manual workflows.



Efficient & meaningful
Patient QA

ArcCHECK®

The Benchmark for 3D Pre-Treatment QA

DIRECT
SunCHECK™
INTEGRATION



- Powerful Patient-Specific QA**
- Recommended by AAPM Task Group 218 for 3D measurement
 - Measures and correlates gantry angle, leaf-end position, absolute dose, and time
 - For all modalities - IMRT, VMAT, SBRT, Tomo, Halcyon and MRgRT QA
 - Works with Enhanced Dynamic Platform (as MotionCHECK™ 3D solution) for QA of systems that perform tumor tracking and dynamic delivery such as the Accuray Radixact® System with Synchrony® and breath-hold gating such as the Radixact System with VitalHold™

- Clinically Relevant Dose & DVH QA**
- Identify TPS and beam delivery errors
 - 1,386 SunPoint® Diode Detectors for increased BEV data density
 - Angular corrections accurate to ±0.5° using the Virtual Inclinometer™
 - Consistent BEV for all gantry angles measuring entrance and exit dose at multiple depths
 - Real-time electrometer measures every pulse

- Tissue Equivalent Inserts**
- Flexible interior dose measurements, supporting heterogeneity tests
 - Inserts mimic: brain, breast, bone, liver, lung, muscle, adipose, titanium, and water/air
 - **MultiPlug™**: Accepts ion chambers, stereotactic detectors and film; offers interior point measurement in 25 unique locations
 - **CavityPlug™**: Simplified isocenter dose measurement, without the film and tissue-equivalent insert features of MultiPlug

- Software Highlights**
- SNC Patient™ software compares measured dose points to planned dose points
 - 3DVH® Software for full 3D QA to support beam model adjustments
 - Direct connectivity with **SunCHECK™ Platform** for expanded pre-treatment QA

- MLC Pattern Machine QA**
- Evaluate discrepancies between planned and delivered MLC patterns

 MR-compatible version available

Device Specifications	
Detector Type	SunPoint® Diode Detectors
Detector Quantity	1386
Detector Spacing (cm)	1.0, 0.7 cm Beams Eye View, 0.5 cm with Merge feature
Array Diameter (cm)	21.0
Water Equivalent Inherent Buildup (g/cm²)	3.3
Detector Physical Depth (cm)	2.9
Array Geometry	Helical Grid (HeliGrid) 1 cm offset
Phantom Material	PMMA (Acrylic)
Active Detector Area (mm²)	0.64
Detector Sensitivity (nC/Gy)	32.0
Max Dose/Pulse (Gy)	0.003
Detector Stability	0.5%/kGy at 6 MV
Dose Rate Dependence	± 1%
Update Frequency (ms)	50
Number of Connection Cables	Single power/data cable
Dimensions (cm³)	27.0 x 43.0
Weight (kg)	15.4

Transport Option
18-inch wide trolley, designed to slide away after positioning on couch; not MR-compatible



CavityPlug™ & MultiPlug™

MapCHECK®3

The Benchmark for 2D IMRT QA



Built for Pre-Treatment IMRT QA

- Most detectors (SunPoint® 2 Diode Detectors) of any 2D array
- Proven stability in large active field size (26 cm x 32 cm)

SNC Patient™ Software Highlights

- Compares dose distribution from plan file to actual measured values
- Highlights points outside acceptance criteria

Address Rotational Beams

- Use with **MapPHAN™**, a water equivalent phantom, for helical and arc-based delivery systems


Device Specifications

Detector Type	SunPoint® 2 Diode Detectors
Detector Quantity	1527
Field Size (cm)	26 x 32
Detector Spacing (mm)	7.07
Active Detector Area (mm x mm)	0.48 x 0.48
Active Detector Volume (mm³)	0.007
Detector Sensitivity (nC/Gy)	15
Sampling Frequency (ms)	50
Detector Stability	1%/kGy at 6 MV
Dose Rate Dependence	±1.5% over the range of 100 cGy/min to 1400 cGy/min
Inherent Buildup (g/cm²)	1.5
Inherent Backscatter (g/cm²)	2.3
Radiation Measured	Photons Co-60 to 25 MV
Number of Connection Cables	Single power/data cable
Dimensions (L/W/H)	56.0 cm x 29.2 cm x 3 cm
Weight (kg)	5.6

Gateway™

NEW

Patient Data Conversion for Pinnacle™ Treatment Planning



Mitigate Information & Network Security Risk

- Eliminate unsupported Pinnacle hardware and software
- Independent of Pinnacle hardware and software

Ensure Consistent Standard of Practice & Quality of Care

- Make legacy Pinnacle patient data accessible in DICOM format for re-treatments
- Converts Pinnacle versions – 4.x to 18.x, native or tar formats
- Further centralize critical data, reducing technical debt and future-proofing patient data for use in analytics or AI/ML model


Software Highlights

- Powered by Oncospace, now part of Sun Nuclear
- Supports 3D, IMRT, VMAT plan types
- Navigate and search Pinnacle archives
- Save to user-provided HD/SAN/NAS or DICOM archive
- Convert on-demand or an entire archive at once
- Requires Windows 10, 11, Server 2022

Plan AI™

NEW

Create Quality Plans, Faster & More Easily



Show Achievable Clinical Plan Quality

- Create patient-specific clinical goals and planning strategy before you begin with DVH Predictions of OAR sparing for prostate, head and neck, thoracic, abdomen, and pelvis radiotherapy*
- Import 'Best Achievable' dosimetric objectives into TPS to drive plan creation
- Enhance Planning Collaboration through Peer Review Features
- Peer review all plans with communication tools and structured checklist

Software Highlights

- Powered by Oncospace, now part of Sun Nuclear
- Access from anywhere via web browser from desktop, laptop or mobile devices
- Comprehensive, collaborative protocol management and plan evaluation tools
- Course Protocol Library provided, representing range of treatment regimens for disease sites; can be used as-is, modified, or to form basis for new protocols
- CT Image + Plan viewer enables navigation and inspection of CT image, structures, and dose distribution
- DVH Evaluation allows at-a-glance comparison of predicted dose if available, clinical goals, and plan results with a DVH display and scorecard
- Varian Eclipse™ and RaySearch RayStation™ Interfaces: Configured scripts will receive DICOM CT and Structure Sets from and import to, a treatment planning system (e.g., predicted dose objectives and other delivery method) to support the creation of a treatment plan

*FDA 510(k) cleared and available only in the United States.

IVD™ 2 with ISORAD™ & QED™

Easy-to-Use In-Vivo Dose Monitoring



Uncomplicated In-Vivo Monitoring

- Wired or wireless versions
- Automatic patient temperature compensation
- QED or ISORAD detector options, with SunPoint® Diode Detectors

Software Highlights

- Use with control module or PC software
- Networkable Microsoft SQL patient database with robust Protected Health Information (PHI) security
- Correction factor tools
- Direct export to Varian Medical Systems® ARIA® Oncology Information System

Detectors

- Flat design for easy placement (QED); Cylindrical design for isotropic response (ISORAD)
- 3 Photon Energy Ranges, 1 Electron Range, and Skin (QED)

Detector Module Specifications

Channels	Standard (rf-IVD 2/IVD 2) 8/4 Standard 4 Maximum 52
Repeatability	± 0.2% or ± 0.1cGy
Polarity	Bipolar (negative or positive polarity detectors)
Leakage	Automatic compensation
Calibration	User calibrated
Warm-up time (sec)	< 30
Wireless frequency (MHz)	USA 916.5; EU 433.92
Power	Rechargeable NiMH battery (12 hr) Power supply
Dimension L/W/H (cm)	7.0 x 12.0 x 3.0
Weight (kg)	0.34

Varian Medical Systems® is a registered trademark, and Varian™, and ARIA® are trademarks, of Varian Medical Systems, Inc. Sun Nuclear Corporation is not affiliated with or sponsored by Varian Medical Systems, Inc.

SRS MapCHECK®

SRS & SBRT QA, No Film



Moving Beyond Film

- Film equivalent SRS/SBRT Patient QA for use with the **StereoPHAN™** end-to-end phantom
- Streamline your workflow from ~300 minutes to ~10 minutes

Irradiate From Any Angle

- Accounts and corrects for angular dependence, field size, and pulse rate
- Ensures accurate dose measurement form any angle, including vertex fields

Flexibility, Speed, & Accuracy

- Detects for output factor, MLC, and grid size errors
- Prevents more common sources of SRS/SBRT treatment errors

Unmatched Detector Resolution

- Detector spacing and resolution specifically designed for SRS/SBRT
- Measures field sizes down to 5 mm (5 diodes in 5 mm cone)
- Supports AAPM TG-101 requirement -- SRS measurements performed with <1 mm detector

SNC Patient™ Software

- Robust angular corrections detect and adjust for translational offset between compared datasets with precision of 0.1 mm (in line with film)
- Guidance for ideal setup of Single-Isocenter Multiple-Target (SIMT) plans (QA Setup tool)
- Offers simplified shifts for occasional larger fields
- Couch kick compatible
- Includes CyberKnife® Machine QA capabilities

Specifications

Detector Type	SunPoint® 2 Diode Detectors
Detector Quantity	1,013
Detector Spacing (mm)	2.47
Active Detector Area (mm x mm)	77 x 77
Detector Sensitivity (nC/Gy)	15
Sampling Frequency (ms)	50
Dose Rate Dependence	+/- 1.0% (100 MU/min to 2400 MU/min)
Inherent Buildup (g/cm²)	2.75
Inherent Backscatter (g/cm²)	2.75
Modalities Supported	Static, rotational, coplanar and noncoplanar (including vertex), CyberKnife® system (including VSI and M6 models with Cones or Incise and MLC Collimators), FFF, cone and MLC fields
Radiation Measured	Photons 6 MV, 10 MV, 6 FFF, 10 FFF
Number of Connection Cables	Single power/data cable
Dimensions (L/W/H)	320 x 105 x 45 (mm)
Weight (kg)	1.9

AVa™ Phantom

SGRT Alignment Verification
StereoPHAN™ Accessory

Comprehensive tracking for SGRT (Surface-Guided Radiation Therapy) systems

- **SGRT-visible and -trackable** surface structures
- **IGRT alignment and verification**, including offset positions
- **IGRT reference point positioning verification** with 3-Axis Off-set StereoPHAN insert



Patent-pending




Stereotactic QA

Meet the stringent demands of stereotactic treatments, with our suite of SRS/SBRT solutions.

Learn more: sunnuclear.com/srsqa





Improving by measuring
Machine QA

StereoPHAN™

Comprehensive End-to-End
Stereotactic QA



Confident Program Commissioning

- Test all aspects of stereotactic planning and delivery
- MRI/CT image fusion, CT to linac patient alignment, and treatment planning QA
- Rotate phantom up to 360° and combine with inserts for sagittal, coronal and transverse plane measurements within 0.1 mm accuracy

Versatile End-to-End Stereotactic QA

- Use with **SRS MapCHECK®** array for film-less, patient-specific QA for challenging small field and MLC-based SRS cases
- Use with **MultiMet-WL Cube** for multi-met single isocenter off-axis verification

Multi-Modality Compatibility

- Supports conventional linacs, CyberKnife® devices, Varian Medical Systems® HyperArc™ Systems, vertex delivery beams, and MRgRT
- SRS headframe compatibility: Brainlab®, Fraxion®, and Leksell Gamma Knife® systems

Specifications

Material	Polymethyl methacrylate (PMMA)
Weight (cylinder, stand, slide)	6.6 kg (15 lbs)
Measurement cubes (mm)	85 x 85 x 85
Dimensions - L/W/H (mm)	522 x 276 x 229

MultiMet-WL Cube

Targeting Accuracy Check
for MultiMet SRS



Single-Isocenter Multiple-Met SRS QA

- Efficiently measures targets up to 7 cm off-axis within 0.1 mm accuracy
- Compatibility with Cone, MLC or Jaw deliveries

User-Friendly Software

- Software identifies off-axis and rotational sources of error – Gantry, Couch or Collimator – in 6 degrees of freedom
- Optimized RT plan enables fast and clinically useful analysis of combined Winston-Lutz results

Versatile Small-Field Tool

- Use with **StereoPHAN** and **SRS MapCHECK** solutions, or as a standalone phantom

Specifications

Dimensions (mm)	85 x 85 x 195
Targets	6 (5 mm diameter) tungsten targets in specified locations
Target to Cross-Hair Tolerance	± 0.1 mm
Target Material	Tungsten Carbide
Quantifiable Off-Axis Accuracy Range	Up to 7 cm

StereoPHAN™ Inserts



Film



Ion chamber



CT/MRI



MRI Signal Generator



Universal Spacer



Multi-film

See more inserts available on sunnuclear.com.

STEEV™ Phantom

Stereotactic End-to-End
Verification



SRS Commissioning & Treatment Verification

- Meet TG-101 requirements for end-to-end SRS commissioning and QA
- Anthropomorphic, tissue-equivalent design accounts for challenging effects of tissue heterogeneity

Accurate Patient Simulation

- Compatible with most positioning and fixation devices
- Internal details (e.g., cortical/trabecular bone, brain, spinal cord, teeth, sinuses, trachea) provide realistic clinical simulation
- Geometric and organic target inserts provide means for comprehensive image QA, geometric machine QA and TPS QA for increased confidence in system performance

Multi-Modality Imaging & (Off) Isocenter Dose Measurements

- MRI/PET/CT inserts include: spherical target, organic targets for deformable image registration, spatial 3D distortion, ISO center
- Inserts include: TLD dosimetry, OSL dosimetry, film dosimetry, film stack dosimetry, film with fiducial, electron density, Winston-Lutz

Specifications
Includes:
Stereotactic Radiosurgery Head
MRI/CT ISO Center rectangular insert
Brain Equivalent Spacer (63.4 x 63.4 x 10 mm)
Brain Equivalent Spacer (63.4 x 63.4 x 20 mm)
Brain Equivalent Spacer (63.4 x 63.4 x 63.4 mm)
Solid Ø 12.7 mm (posterior chamber access plug)
Solid Ø 12.7 mm anterior chamber access plug with MRI/CT fiducial
Neck Alignment Plate & Rubber Clamp

SRS MR Distortion Phantom

Assess MR Image Distortion
in SRS Planning



Characterize Geometric Accuracy for MR use in Treatment Planning

- Assess MR image distortion in SRS planning
- Realistic anthropomorphic scenario for CT and MR imaging
- Presents simulated bony anatomy as rigid landmarks for image fusion
- Special pads compatible with all fixation frames
- CT/MR markers facilitate positioning and image registration

Optimizing SRS QA

- Verify image fusion and deformable image registration algorithms used in various treatment planning systems
- Tissue equivalent, anthropomorphic phantom

Distortion Check Software

- Detects physical control points (859) throughout the 3D image volume
- Cloud-based solution designed to quickly and automatically quantify distortion in MR images

Specifications	
Dimensions	32 cm x 24 cm x 18 cm
Weight	12 lbs (5.5 kg)
Materials	Skull: Plastic-based bone substitute; Interstitial/ Soft tissues: Water-base polymer; Grid: Reinforced nylon
Software	Distortion Check software
Model 603-GS Includes	
1	MR Distortion & Image Fusion Head Phantom
1	ABS Cradle
Unlimited	Unlimited scans using MRI Distortion Check Software for initial 2 year period
1	Custom Carry Case

IC PROFILER™

Real-Time, Tankless Beam Scanning



Monthly & Annual QA in Minutes

- A single measurement provides real-time beam performance data, including:
 - Constancy checks for output and beam quality
 - Flatness, symmetry, field size and penumbra width

The Water Tank Alternative

- Accurate within 0.5% to a water tank
- Sets up in minutes, with no warm-up or pre-irradiation needed
- Linac acceptance, routine QA, and more

SunCHECK Integration

- Direct connectivity with **SunCHECK™ Platform** for efficient Monthly and Annual QA




MR-compatible version available

Device Specifications

Detector Type	Parallel plate Ion Chamber
Detector Quantity	251 total; X Axis: 63; Y Axis: 65; -Diagonal: 63; +Diagonal: 63
Detector Spacing (mm)	5.0
Array Size (cm)	32.0 x 32.0
Detector Volume (cm³)	0.046
Detector Sensitivity (pC/cGy)	14.4
Inherent Buildup (g/cm²)	0.94
Inherent Backscatter (g/cm²)	2.3
Phantom Material	PMMA (Acrylic) / PC
Weight (kg)	8.8

Quad Wedge Plates

Simplified Beam Energy
Verification



Accelerate Beam Scanning

- Use with **IC PROFILER™** array for fast, precise energy measurements
 - Quad Wedges Plates are not suitable for use with IC PROFILER™-MR array
- Easy, reproducible setup
- Maximum efficiency compared to Solid Water (~15 minutes for 5 beams vs. ~60 minutes)

Photon & Electron Measurement

- Supports a wide range of energies for photons and electrons

Specifications	
Electron Energy Quad Wedge Plate	Aluminum-based design; Suitable for analysis of energies from 4-22 MeV
Photon Energy Quad Wedge Plate	Copper-based design; Suitable for analysis of energies from 6-18 MV

Daily QA™ 3

Daily Beam Quality Analysis
in One Measurement



DIRECT
SunCHECK™
INTEGRATION

Fast Daily Checks of Energy Constancy, Beam Quality

- After daily test beam delivery see results for: dose output, beam flatness, beam symmetry, beam energy, light-radiation field coincidence, shape constancy, and field size shift for FFF

Efficient, Independent Beam Delivery Error Detection

- Daily test templates are easy for physicists to setup and handoff to therapists
- Fast and simple set up Rotational and FFF beams are supported, with no warm-up or pre-irradiation needed, and no additional trips to the vault
- Power Data Interface (PDI) managed through single-cable architecture
- Wireless option available – eliminates cable connections by using rf connections

SunCHECK Integration

- Direct connectivity with **SunCHECK™ Platform** for efficient Daily QA
- Pre-configured TG-142 tests, tolerances and categories
- Safety, MLC and imaging tests reside in same database
- Connect device and data is collected automatically (no manual entry)

Specifications

Detector Type	SunPoint® Diode Detectors Vented Ion Chambers
Detector Spacing (mm)	Diodes 5.0
Chamber Active Volume (cm³)	Electron 0.6; Photon 0.3
Field Size (cm)	20 x 20
Inherent Buildup (g/cm²)	Chambers 1.0 ± 0.1
Inherent Backscatter (cm)	2.3
Electron Energy Attenuation	Air, Cu, Al, Fe
Radiation Measured	Electrons, 4 MeV to 25 MeV; Photons, Co-60 to 25 MV
rf Frequency (rf-Daily QA 3) (GHz)	2.400 to 2.485
Dimensions L/W/H (cm)	25.6 x 40.8 x 4.6
Weight (kg)	5.7
Number of Connection Cables	Single power / data cable

 MR-compatible version available

Solid Water® HE

Reliable, Durable Water
Equivalent Phantoms



Photon & Electron Energy Measurements

- Mimics true water within 0.5% for accurate calibration of radiotherapy beams
- Exceptional, verified slab uniformity
- 30 cm or 20 cm slab kits, designed to fit **MapCHECK® 3** and **IC PROFILER™** arrays, available for measuring output with a wide range of energies
- Individual slab thicknesses from 0.1 cm to 6.0 cm available

Specifications

Depth Ionization Relative-to-water

Photons	1.000 +/- 0.005
Electrons	1.000 +/- 0.005

Density

Mass Density (g/cm³)	1.032 +/- 0.005
Electron Density (e⁻/cm³ N _A)	0.557 +/- 0.001
Solid Water HE / Water	1.000 +/- 0.005
Electron Density Ratio	



 MR-compatible



MR-Guided RT QA


Address the unique challenges magnetic fields
present, with custom-designed QA solutions.

Learn more: sunnuclear.com/mrqa



Dynamic Thorax Phantom

Analyze Image Acquisition, Planning & Dose Delivery Verification



Motion IGRT & IMRT QA

- Comprehensive analysis of image acquisition, planning and dose delivery in IGRT
- Investigating and minimizing the impact of tumor motion inside the lung
- 3D tumor motion within tissue-equivalent phantom, representing lung
- Sub-millimeter accuracy and reproducibility
- Surrogate breathing platform accommodates numerous gating devices
- A Deviceless 4D CT add-on is available for users of the Smart Deviceless 4D system from GE Healthcare

Tissue-Equivalent Lung Phantom

- Tissue equivalent from 50 keV to 125 MeV
- Compatible with TLD, MOSFET, nanodot™, microchamber, PET/CT targets and film

XSight® Lung Tracking Phantom Kit

- Utilizes a specialized phantom body verified and validated by Accuray for use with CyberKnife® systems
- Designed to work in conjunction with the Synchrony® motion synchronization technology


Motion Control Software

- Enables different cycles, amplitudes and waveforms
- Graphical, intuitive user interface

Specifications	
Dimensions	67 cm x 32 cm x 28 cm (26" x 13" x 11")
Weight	17.2 kg (38 lb)
Amplitude, IS	± 25 mm
Amplitude, AP/LR	± 5 mm
Amplitude, Surrogate	± 25 mm
Motion Accuracy	± 0.1 mm
Cycle Time	1 - ∞ (adjusted based on amplitude)
Waveforms	sin (t), 1-2cos4(t), 1-2cos6(t), sawtooth, sharkfin

Enhanced Dynamic Platform

Programmable Motion for Tracking & Positioning



Highlights

- Works with ArcCHECK® (as MotionCHECK™ 3D solution) for QA of systems that perform tumor tracking and dynamic delivery such as the Accuray Radixact® System with Synchrony® and breath-hold gating such as the Radixact System with VitalHold™
- Builds upon the Dynamic Platform, with sub-millimeter accuracy for 3D Motion QA of systems that perform tumor tracking and gating
- Easily set up for 1D, 2D or 3D motion QA
- Inferior-superior motion up to +/- 25mm (50 mm total) for applicable phantoms up to 70 lb.
- An 11.3° inclined plane provides +/- 5.0 mm (10 mm total) of motion in posterior-anterior direction (for applicable phantoms up to 50 lb).
- 30° rotation about the linac couch provides +/- 12.5 mm (25 mm total) of lateral motion
- Surrogate platform simulates posterior-anterior chest wall motion of +/-25mm (50mm total)
- Includes Motion Control Software

General Specifications

Dimensions (cm)	92.8(L) x 37.5(W) x 27.5(H) (for all motions at home position)
Weight (kg)	18.4
Position Accuracy (mm)	Position Accuracy (-/+0.25 mm)
Maximum Amplitude Inf/Sup (mm)	+/- 25.0 (50 total)
Maximum Amplitude Lateral (mm)	+/- 12.5 (25 total)
Maximum Amplitude Pos/Ant (mm)	+/- 5.0 (10 total)
Maximum Amplitude Surrogate (mm)	+/- 25.0 (50 total)
Editable Built-In Waveforms	sin(t), 1-2cos4(t), 1-2cos6(t), sawtooth, sharkfin
Power	110-250 VAC, 50/60 Hz

TomoDOSE™

Diode Detector Array for TomoTherapy® Systems



TomoTherapy System QA

- Supports routine QA, daily QA, and post-component replacement QA
- Measures entire Hi-Art beam in a single measurement, including 1 X-axis and 9 Y-axis

Accessible Data

- Access to raw data and import water tank data for comparison with TomoDose files

General Specifications

Detector Type	SunPoint® Diode Detectors
Detector Quantity	223 total on X and Y
Detector Spacing (mm)	X 5.0, Y 4.0, Y Off-axis 8.0
Field Size (cm)	53.0 x 9.8
Array Length (cm)	X 53.0 Y 9.8 (8.0 at ±19.0)
Y Axes Offset (cm)	±5.0, ±10.0, ±15.0, ±19.0 cm
Inherent Backscatter (g/cm²)	2.3
Active Detector Area (mm²)	0.64
Detector Volume (cm³)	0.000019
Detector Sensitivity (nC/Gy)	32.0
Detector Stability	0.5%/kGy at 6 MV
Maximum Dose Rate Limit (Gy/min)	56.0
Operating System	Windows 2000, XP 32-bit, or Vista 32-bit
Dimensions L/W/H (cm)	25.6 x 52.0 x 6.0
Weight (kg)	5.0
Number of Connection Cables	Single power/data cable

Daily ISO Phantom

Daily Isocenter Checks Made Easy



Efficient Daily Alignment Verification

- Ensure isocenters match for imaging modalities, lasers, and surface-guided alignment systems
- Machined concentric circle targets to objectively assess setup errors, including rotations, to easily align to true isocenter
- Unique fiducials produce sharp clear images in EPID, kV and CBCT imaging

Easy, Precise Shifting

- Available 6DOF ISO Base provides known phantom translations and rotations to check corrections made by 6DOF couches
- Manufactured with machining tolerance of ± 0.02 mm and target positioning accuracy of ± 0.1 mm

Analysis Software


- Enables user-friendly quality control of linac isocenters by analyzing DICOM images acquired with the EPID, kV and CBCT

Specifications

Alignment System	Engraved markings, concentric alignment circles and internal radiographic markers/targets compatible with CBCT, MV-EPID, kV imaging, 6D couches and more
Isocenter Marker	6.35 mm diameter low-Z ceramic bead
Offset Marker	6.35 mm diameter low-Z ceramic bead at a fixed offset from isocenter, for registration and repositioning
Light Field Test	Verified using integrated radiographic markers and external scribe lines corresponding to a 10 cm x 10 cm light field
Bases	6DOF ISO Base™ designed for positioning, leveling and quick calculation of complex 3D shifts of systems with integrated 6DOF robotic couch. ISO Base™ positions and levels Phantom on 3DOF (conventional) systems. Both contain integrated pixel calibration targets recognized by ISO Analyze™ software.
Dimensions	12 cm x 12 cm x 12 cm
Weight	1.7 kg

RapidCHECK™

Automated CT-to-Density Calibration
& CT Image Quality Analysis



Automate QA Workflows

- Use with **Advanced Electron Density Phantom** for faster, less-tedious calibration of CT-to-electron density tables
- Use with **CT ACR 464 Phantom** to automate image quality analysis faster analysis, trending reports, and an easily searchable permanent record
- Use with **IQphan Phantom** to quickly process CT data into results and reports

Browser-Based Software

- Use RapidCHECK software from any browser in your clinical network
- Get results immediately, load data, and see analysis

Specifications

Operating System	Windows 10 (Pro, Enterprise, and Educational) or Windows 11 (Pro, Education, Enterprise, Pro Education) with either Microsoft Edge or Google Chrome browsers, with at least an i3 processor, 8 GB RAM, and 10 GB of drive space
Regional Settings	US or International
Minimum Computer Specifications	Intel i3 processor; total RAM 4 GB (8 GB recommended); 10 GB of drive space; Display resolution 1280 x 1024; Color depth 32-bit
Browser	Google Chrome (recommended) or Microsoft Edge

Advanced Electron Density Phantom

Tissue-Equivalent CT-to-Electron Density Calibration



Automated CT-to-Electron Density Analysis

- Patented rod markers* uniquely identify each material in a CT scan
- CT-to-density tables are automatically generated in the **RapidCHECK™** software

Sized for Wide-Beam Applications

- Larger phantom body diameter supports evaluation of cone-beam CT and wide-beam CT scanners
- Removable section for head and small body protocols



Superior Tissue Equivalence & Chamber Compatibility

- Meets medical standards ICRU-44 and ICRP for human tissue densities
- Constructed with Solid Water® background material
- Compatible with any ion chamber

Specifications

In-plane Dimensions	40.0 cm (15.7 in) x 30.0 cm (11.8 in)
Depth	16.5 cm (6.3 in), up to 26.5 cm (10.2 in) with optional extension plates
Removable Head Section Diameter	20.0 cm (7.87 in)
Material	HE Energy-matched CT Solid Water® phantom material
Interchangeable Inserts	14 solid inserts plus two true water containers
Optional Inserts	Aluminum, Stainless Steel, Titanium
Available Upon Request	Extension plates, Ion Chamber conversion rod
Weight	15.5 kg (34.1 lbs)
Wheeled Case	Included
Stand	Included

*U.S. Patent No. 10,939,891



Varian Medical Systems® Halcyon™ System & Ethos™ Therapy QA

We offer a range of independent QA solutions for these well-adopted platforms.

Learn more: sunnuclear.com/halcyonqa



Varian Medical Systems® is a registered trademark, and Varian™, Halcyon™, and Ethos™ are trademarks, of Varian Medical Systems, Inc. Sun Nuclear Corporation is not affiliated with or sponsored by Varian Medical Systems, Inc.

SunSCAN™ 3D

Next-Generation Cylindrical
Water Scanning System

User-Centered Design

- Faster, easier commissioning and beam scanning, with SRS-class accuracy
- Unique cylindrical shape removes need for tank shifts, which take time and compromise scanning setup
- Single Setup
 - 65 cm scan range allows 40 x 40 cm field scans, even at 100 cm SSD and 40 cm depth
- Consistent Detector Orientation
 - Smallest part of the detector always measures the beam edge, minimizing stem and cable effects and water movement
- Virtual Reference Detector using Pulse Normalization permitting accurate scanning of small fields without the need of a physical reference detector

7-Minute AutoSetup™

- Automatic setup in a third of the time of other tanks
- Tank is leveled and aligned, with detector positioned at water surface, in minutes
- True, physical leveling enables the most accurate scans and is achieved through a proven guided workflow

Intuitive Software

- New SunDOSE™ software reduces clicks to complete commissioning, and features favorite and enhanced workflow features
- AutoSetup routine guides users through tank setup



“With SunSCAN 3D, in form and function, it’s clear Sun Nuclear put thought into every detail to help medical physics teams work smartly. It’s easy to set up, fill and drain. Plus, it’s light and compact for moving and storing. Above all, it offers high accuracy for confidence in your commissioning and annuals.”

Kayhan Mohajeri, M.S., DABR,
Medical Physicist



General Specifications

Vertical (mm)	400
Diameter (mm)	650
Ring (Degrees)	360
Motors	Encoded stepper/servo
Scanning Modes	Continuous and step
Scanning Speed Range (mm/sec)	Variable up to 20
Scanning Accuracy (mm)	0.1 throughout the 3D volume
Repeatability (mm)	0.05
Position Resolution (mm)	0.02

Water Tank

Thickness Wall/Bottom (mm)	13/19
Height (mm)	916
Width (mm)	736
Diameter Inner (mm)	676
Water Capacity (L)	172
Weight Empty/Full (kg)	59/194
Linac Pulse Count	Included with threshold detection

Software

Tank Centering	Automatic
Leveling	Automatic
Surface Detection	Automatic
TPS Export	Included

Maximize accuracy,
minimize subjectivity
Dosimetry



Control Center with Integrated Electrometer


Highlights

- Improved Signal to Noise Ratio for superior small signal measurements
- Dual bias control, compatible with most detectors
- Enhanced Dynamic Mode automatically adjusts to signal - no need to set gain

SunDOSE™ Software

Highlights

- Easily move between tasks with intuitive interface
- With visualization of all layers, users can see processing applied on each scan, and batch process similar scan types with one click
- Live Scan QA and TPS Model QA for maximum confidence in scanning data



SunSCAN™ TPR

Highlights

- Supports Varian Medical Systems®, Elekta, Siemens and CyberKnife® delivery systems
- Less than 5-minute installation with no additional tools
- 20 cm TPR drain measurement in 2.5 minutes
- 20 cm TPR fill measurement in 3.5 minutes



Digital Pendant

Highlights

- Two interchangeable pendants on tank and reservoir
- Easy-to-read backlit display
- Intuitive controls for tank, lift and reservoir
- Interlock prevents accidental irradiation



Reservoir

Highlights

- Redesigned with half the footprint
- Dripless tank connector and self-enclosed hose avoid spills



Mini-Lift Table (MLT)

Highlights

- Integrated Automatic Leveling Platform
 - Leveling to within <0.02 degrees
 - Centering to within <0.1mm
- Straddles linac couch ring for stability
- Fits through standard doorways; legs fold for storage
- Quick and easy disassembly for transport



SunSILICON™ & SunSILICON™ P Detectors
Optimized for Precision in Relative Photon and Electron Dosimetry

NEW



Designed for Advanced Relative Dosimetry in Cylindrical Water Phantoms

- Compatible with SunSCAN™ 3D and 3D SCANNER™ systems; suitable for IMRT, SRT, and IGRT techniques
- Custom, fully guarded p-type silicon diode
 - Small active volume of 0.053 mm³ for high spatial resolution
 - High sensitivity for faster scanning speeds
 - Leading radiation hardness and leakage characteristics for better data quality
- Water equivalent housing using HE Solid Water®
- Clearly marked housing for simplified setup
- Consistent detector-to-detector performance enabled by tighter mechanical tolerances
- Low dose per pulse dependence

SunSILICON (Model 1048)

- An **unshielded diode** ideal for very small photon fields and electron dosimetry

SunSILICON P (Model 1049)


- A **shielded diode** optimized for small to large photon fields

Specifications

Field Size Range	SunSILICON: (1 x 1) cm² to (10 x 10) cm² (photons); (1 x 1) cm² to (40 x 40) cm² (electrons) SunSILICON P: (2 x 2) cm² - (40 x 40) cm² (photons)
Smallest Field Size*	SunSILICON: (0.4 x 0.4) cm² SunSILICON P: (1.2 x 1.2) cm²
Sensitivity	SunSILICON: 36 nC/Gy SunSILICON P: 38 nC/Gy
Impedance	> 1000 MΩ
Water Equivalent Build-up	1.25 mm

* Refer to IAEA TRS-483 or AAPM TG-155 for the methodology of applying field output correction factors to ensure high-accuracy output factor measurements in very small photon fields.

ATOM® Phantom Family
Versatile Dosimetry Investigation & Verification



Highlights

- Full line of anthropomorphic, cross-sectional dosimetry phantoms, consisting of five clinically relevant ages
- Uniquely designed for investigation of organ doses and whole body effective doses, as well as the verification of therapeutic radiation doses
- Produced with average soft tissue, average bone tissue, cartilage, spinal cord, spinal disks, lung, brain, and sinus tissues

Linear Attenuation of Simulated Tissues

- Within 1% of actual attenuation for soft tissue and bone
- Within 3% for lung, from 50 keV to 15 MeV
- Lung tissue is a low-density inhale formulation equivalent to 0.2 g/cc

Homogenous Bone

- Uses age-specific, averaged mineral density of cortical and trabecular bone ratios to create a homogenous bone, with no distinction in the anatomy
- Eases comparative Monte-Carlo calculations for dose verification
- Makes red-marrow measurements in electron equilibrium easier to obtain

1D SCANNER™

Accurate Point Dose & PDD Dosimetry Water Tank



DIRECT
SunCHECK™
INTEGRATION

Simple, Efficient Water Scanning

- Perform dosimetry measurements in water, including output factors, dose calibrations, annual, and routine QA
- Collect PDD curves with optional SunDOSE™ or SNC Dosimetry™ software and **PC Electrometer™**

Easy, Reproducible Setup

- Single power and data cable connection
- Water surface detection feature automatically sets the dosimetry detector at the water surface

Software

- Organize and execute groups of scans
- 1-click quantitative analysis across data sets
- Easy, searchable access to data

Specifications	
Inner Dimensions L/W/H (cm)	35.0 x 39.0 x 36.2
Exterior Dimensions L/W/H (cm)	37.6 x 40.6 x 36.8
Interior Volume	50 liters at 35 cm depth
Weight empty with arm (kg)	10.4
Arm positioning increments (cm)	0.01, 0.1, 1.0 & 10.0
Arm positioning accuracy (cm)	± 0.01; ± 0.02 for movements of 10 cm
Scan depth maximum (cm)	30.0
Operating system	Windows 10 Pro 64-bit
Number of connection cables	Single power/data cable

PC Electrometer™

Portable, Reference-Class Electrometer



DIRECT
SunCHECK™
INTEGRATION

Accurate & Convenient

- Dual channel reference class electrometer for absolute dose calibration
- Available in BNC or TNC triax connectors

Simple & Portable

- Small and lightweight for easy transport
- Simple setup with single USB and < 1-minute warm-up time

Software

- Organize and execute groups of scans
- 1-click quantitative analysis across data sets
- Easy, searchable access to data

Specifications	
Warm Up Time	< 1.0 min
Charge Range	2 pC – 10 mC, 15 fC resolution
Current Range (Continuous)	Low 2 pA – 50 nA
Current Range (Pulsed)	0 -105 pC/pulse
Leakage Drift	±0.001 pA
Display Update Frequency(s)	500 ms
Bias Voltage	Adjustable, 0 to ±400 V
Non-linearity	± 0.1% of full scale
Long-Term Stability	< ± 0.5%
Measurement Repeatability	± 0.25% of full scale
A/C Converter	16-bit
Operating System	Windows 10 Pro 64-bit
Dimensions	10.6 x 14.8 x 4.5 cm
Weight	0.46 kg
Compatibility	SunDOSE or SNC Dosimetry software
Conformity	Reference class according to IEC 60731

Reference Detector

Interference-Free Dosimetry Scanning



Small Field Annuals & Commissioning

- Linac head leakage allows the Reference Detector to obtain a reference signal during water tank scanning of photon energies
- Use with Sun Nuclear water tank for commissioning measurements of any field size
- Fully out-of-field detector is ideal for small fields

Easy & Efficient

- Mounts to top surface of a supported linac gantry using a non-invasive dual-lock fastener
- Includes 2-meter cable with triax connector

Specifications	
Volume (cc)	39
L x W x H (mm)	125 x 105 x 15
Reference Point (mm)	2-meter cable with triaxial connector
Placement	Top surface of linac head, via dual-lock fastener

SNC125c™

Reference Class Dosimetry

Reliable & Accurate Reference Dosimetry

- Vented, waterproof and fully guarded
- Reduces the convolution of high-dose gradient regions during profile and depth measurements

Ion Chamber Highlights

- Meets IEC 60731 standards
- k_Q factors available for TG-51, TRS398 and DIN 6800-2 calibrations
- Sensitivity of a 0.125 cm³ chamber and penumbra closer to a micro-chamber

EDGE Detector™

Ultimate Small Field Detector for Precision 3D Dosimetry



Well-Suited for Small Fields

- SunPoint® Diode Detector is 842 times smaller, and has 100 times more signal, than micro ionization chambers
- Small size ideal for accurate penumbra characterization
- Also ideal for steep gradients for fields ≤10 cm

Compliance

- Supports compliance with TRS483 and precision dosimetry

Specifications	
Active Detection Area (mm)	0.8 x 0.80.3 from top, 4.72 from end
Diode Die Location (mm)	2.7 from side; location is indicated by cross hairs on top of the housing
Water Depth Equivalent (mm)	0.5
Housing Wall Thickness (mm)	0.13 brass
External Dimensions (mm)	3.8 x 5.5 x 38
Nominal Sensitivity (nC/Gy)	32.0
Impedance (Mohm)	>200 at 10 mV reverse bias
Output Polarity	Negative
Cable	3.4 mm dia. x 1.8 m long, triax
Cable Connector	BNC or TNC triax, or adapters upon request

Specifications	
Active Volume (cm³)	0.108
Active Length (mm)	7.05
Active Diameter (mm)	4.75
Sensitivity (nC/Gy)	3.4
Wall Material	Paint 0.05 mm PMMA 0.30 mm Graphite 0.25 mm
Electrode	0.8 mm diameter aluminum
Polarizing Voltage	±400 V Max
Cable Length (m)	1.5
Cable Connector	TNC or BNC

See sunnuclear.com for specifications.

SNC350p™

Electron Reference Dosimetry



Reliable & Accurate Reference Dosimetry

- Vented, waterproof and fully guarded
- Parallel-plate ion chamber is well-guarded to minimize perturbation effects for reference, field, and scanning dosimetry of therapeutic electron beams, TDD/TPS commissioning and QA

Ion Chamber Highlights & Compliance

- Supports absolute or relative dose point measurements and PDD measurements
- Conforms to the design principles as stated by Dr. M. Roos et al. (IAEA TRS-381)
- Meets AAPM TG-51 and IAEA TRS-398 requirements for low-energy beams (<10 MeV)

Specifications	
Sensitive Volume (cm³)	0.388
Entrance Window (mm)	0.05 Paint; 1.00 PMMA; 0.02 Carbon
Reference Point (mm)	1.0 Below Window Surface
Collection Volume Height (mm)	2
Collector Diameter (mm)	15.6
Guard Ring Width (mm)	4.1
Polarity Effect	Within 1.000 (±) 0.01
Waterproofing	Viton tubing
Max Dose Rate for (Gy/s)	
≥ 99.5 % Saturation	5.2
≥ 99.0 % Saturation	10.4
Max Dose Per Pulse for (mGy)	
≥ 99.5 % Saturation	0.46
≥ 99.0 % Saturation	0.92
Radiation Quality	Photons Co-60 to 25 MV Electrons 5 MeV to 25 MeV
Field Size (mm)	Minimum 40 x 40 Maximum 400 x 400
Sensitive Volume (cm³)	0.388
Entrance Window (mm)	0.05 Paint

SNC600c™

Photon & Electron Reference Dosimetry




Reliable & Accurate Reference Dosimetry

- Vented, waterproof and fully guarded

Ion Chamber Highlights

- Based on the classic Farmer Chamber design
- k_Q factors available for TG-51, TRS398 and DIN 6800-2 calibrations
- Design allows use in most slab phantoms
- Reference class performance (IEC 60731) allows for use in X-ray and electron reference dosimetry protocols - TG-51 and TRS-398



Specifications	
Active Volume (cm³)	0.6
Active Length (mm)	22.7
Active Diameter (mm)	6.1
Sensitivity (nC/Gy)	20
Wall Material (mm)	Paint 0.05, Graphite 0.43
Energy Range	Co-60 - 25 M; V9 MeV - 25 MeV
Electrode (mm)	1.1 diameter aluminum
Vented	To atmosphere through waterproof tubing
Waterproofing	Viton tubing
Buildup Cap (mm)	4.5
Polarizing Voltage	±400 V Max
Length (m)	1.5
Cable Connector	TNC or BNC



Motion QA

Meet the exacting requirements of Motion QA with our comprehensive range of products designed for this purpose.

Learn more: sunnuclear.com/motion



Industry-standard solutions
and innovations for
Diagnostic QC

Doppler Ultrasound Phantoms

Reproducible System Velocity Testing



Comprehensive QA & Testing

- Determine maximum signal penetration, channel isolation, and flow rate readout accuracy
- Doppler flow and B-Mode QA test systems
- Meet ACR, ECR, and AIUM QA requirements
- **Doppler 403™ Flow Phantom** ideal for abdominal flow measurements
- **Mini-Doppler 1430™ Flow Phantom** ideal for cardiology and musculoskeletal applications

Unparalleled Tissue Mimicking

- Blood-mimicking fluid ultrasonically similar to human tissue, with an electronic flow of 1550 m/s
- Patented High Equivalency Gel* (HE Gel™) offers tissue mimicking for evaluating image uniformity, detecting dead transducer elements, and assessing maximum penetration depth

Specifications

HE Gel™ Multi-Frequency Tissue-Mimicking Material	Included
Composite Film Scanning Surface	Included
Vessels (2)	5 mm inner diameter; 1 horizontal at 2 cm depth, 1 diagonal at 40° from 2 to 16 cm deep (403)
	4 mm inner diameter; 1 horizontal at 2 cm depth, 1 diagonal at 35° from 2 to 9 cm deep (1430)
Flow Rates	Customizable, constant and pulsatile
Blood Mimicking Fluid	Speed of Sound 1550 +/- 10 m/s
Targets	Strings, cysts, greyscale, resolution groups
Dimensions (Case)	28 H x 30.5 W x 22 cm (403)
	20 H x 23 W x 15.2 cm (1430)
Weight	8.34 kg (403)
	4.6 kg (1430)

*U.S. Patent No. 6,352,860

B-Mode Ultrasound Phantoms

Training & Compliance Ultrasound Testing



Comprehensive Offerings

- Comprehensive Ultrasound QA solutions from Sun Nuclear for training through compliance and more
- Sun Nuclear patented* HE Gel™ and Zerdine® Hydrogel provide multi-frequency, high quality, reproducible images

Comprehensive QA Test Coverage

- Meet ACR, AIUM, AAPM and IEC TS 62736:2016 requirements
- Test across the entire frequency range (2 - 18 MHz)
- **Model 40GSE** Multi-purpose, multi-tissue phantom with elastography and dual attenuation zones
- **Sono403™**: Multi-purpose phantom ensures accurate screening, diagnosis and monitoring
- **ATS 539**: Multi-purpose phantom of durable urethane construction; low-cost QA solution for compliance tests
- **ATS 570**: Multi-purpose, endoscopic phantom with curved scan surface and endocavity well for enhanced testing of curved probes and endo probe

Basic QA Test Coverage

- Provide support for compliance tests; limited ability to support other recommended QA tests
- Test across the entire frequency range (2 - 18 MHz)
- Dedicated Ultrasound image uniformity phantoms

See sunnuclear.com for a full listing of Ultrasound QA solutions, including Small Parts and Special Purpose phantoms and detailed specifications.

CT ACR 464 Phantom

Multi-Modality CT Accreditation



Comprehensive CT Testing

- Test positioning and alignment accuracy, CT number accuracy, slice thickness, low contrast detectability, image resolution and uniformity, spatial resolution, and inter- and intra-plane distance measurement accuracy
- Meet AAPM TG-66 requirements


Proven & Versatile Design

- Made of the original Solid Water® Zero HU formulation
- Works with **RapidCHECK™** software to automate CT image quality testing or analysis with the SunCHECK(R) Platform
- Optional Phantom Body Ring and Extensions available

See sunnuclear.com for specifications.

IQphan™

Comprehensive CT Image Quality Phantom



Comprehensive CT QA — All in One Phantom

- Perform QA across CT imaging systems, from sophisticated diagnostic scanners to cone beam to on-board radiotherapy systems
- Use with **RapidCHECK™** Image Quality Analysis software for exacting CT imaging quality testing, with quick, consistent analysis

Modular Testing Support

- High-Contrast Resolution Module features high-resolution line pairs, large 3D patterns that are easy to visualize, and robust data analysis in **RapidCHECK** software
- Slice Thickness & Geometric Evaluation Module with multiple wire-ramp materials and diameters enable analysis of slice thickness on range of scanners -- from diagnostic CT to CBCT and MVCT
- Low-Contrast Detectability Module provides a low-contrast test covering radiation therapy systems and diagnostic CT
- Uniformity Module supports assessment of noise and uniformity in HE CT Solid Water
- HU Module tests the consistency of known HU materials and measures the effective energy of the scan

See sunnuclear.com for specifications.

Multi-Energy CT Phantom

Comprehensive Spectral Testing, Tissue Equivalence



Comprehensive Testing of Scanner Performance

- Test efficacy of clinical protocols over an expanded range of material concentrations for multi-energy analysis
- Compare consistency and stability across scanners
- Expanded range of testing to exceed draft AAPM Task Group 299 requirements

Automated Material Discrimination

- Solid rods represent iodine, calcium, blood, adipose, and more
- Patent-pending rod markers enable automated analysis

Specifications	
In-Plane Dimensions	40.0 cm (15.7 in) x 30.0 cm (11.8 in)
Depth	16.5 cm (6.3 in), up to 26.5 cm (10.2 in) with extension plates
Removable Head Section Diameter	20.0 cm (7.87 in)
Material	HE CT Solid Water® phantom material
Interchangeable Inserts	27 solid inserts plus 1 true water container, each tagged with a CT-visible rod identification code
8 HE Iodine Inserts with Variable Concentrations	Concentrations of 0.2, 0.5, 1.0, 2.0, 5.0, 10.0, 15.0, and 20.0 mg/mL
3 Iodine Inserts with Variable Diameters	5.0 mg/mL concentration at diameters of 2.0, 5.0, and 10.0 mm
8 HE Calcium Inserts	Concentrations of 0, 5, 10, 20, 50, 100, 200, and 300 mg/mL
3 Blood [iron] Inserts	Blood-mimicking material at relative electron densities of 1.03, 1.07, and 1.10
2 Blood [iron] with Iodine Inserts	Blood-mimicking material plus iodine at 2.0 and 4.0 mg/mL
3 Tissue-Mimicking Inserts	High-Equivalency Brain, High-Equivalency Adipose, High-Equivalency CT Solid Water
Weight	15.5 kg (34.1 lbs)
Wheeled Case	Included
Stand	Included

Mercury 4.0 Phantom

Advanced CT Performance Assessment



Characterize Advanced CT Features

- Address performance and effectiveness of Automatic Exposure Control/Tube Current Modulation
- Evaluate image quality for Iterative Reconstruction
- Meet AAPM TG-233 requirements

CT Protocol Optimization

- 5-tiered sections reflect range of patient sizes, and enable size-dependent image quality evaluation
- Software analysis, featuring imQuest software available from Duke University

Specifications	
Material	Polyethylene
Diameter	16.0, 21.0, 26.0, 31.0, and 36.0 cm
Length	52.0 cm
Contrast Materials	HE CT Solid Water®, Bone Mimicking Material, Polystyrene, 10 mg/mL Iodine, and Air
Resolution Wedge	HE CT Solid Water® phantom material
Software Analysis	Works with imQuest software, available from Duke University
Included	Wheeled Case and Stand


RapidCHECK™ Software

Automated CT-to-Density Calibration & CT Image Quality Analysis

Automate QA Workflows

- Use with **IQphan Phantom** to quickly process CT data into results and reports
- Use with **Advanced Electron Density Phantom** for faster, less-tedious calibration of CT-to-electron density tables
- Use with **CT ACR 464 Phantom** for automation of image quality analysis, trending reports, and an easily searchable permanent record

See [p.34](#) to learn more.



CTDI Phantoms

Computed Tomography Dose Index Phantom




Compliance Maintenance

- Measure absorbed dose and monitor scanner output for Dose Index QA
- Meet AAPM TG-66 requirements
- 2 and 3-piece configurations available
- Nested modules adapt the phantom to the size required by user protocol

Specifications	
Material	Polymethyl-Methacrylate (PMMA/Acrylic)
Density	1.19 g/cm³
Alignment Markings	Etched lines centered on all three planes
Module	Dimensions (OD x Length)
Adult Body	32 cm x 14.5 cm
Adult Head/Pediatric Body	16 cm x 14.5 cm
Pediatric Head (Model 468-BHP only)	10 cm x 14.5 cm
Chamber Ports Diameter	1.31 cm

CT Perfusion Phantom

Optimize Imaging & Perfusion Protocols



Consistent, Optimized CT Perfusion Programs

- Ensure your CT scanner and perfusion software are providing consistent results by benchmarking perfusion rates and time-attenuation curves
- Use the dose port to optimize imaging and perfusion protocols

Specifications	
Covers and housings	PVC, Acrylic
Dosimetry Port	Standard CT Pencil Chambers
Central Scan Disk	High Equivalency (HE) Brain Mimicking Material
Artery and Vein Rods	16 discrete sections of blood and contrast simulating materials to mimic arterial flow and delayed venous flow rates following a contrast bolus injection
Brain Tissue Rods (Qty 2)	16 discrete sections of brain tissue to mimic tissue uptake rates following a contrast bolus injection
Velocity settings (mm/second)	1.31, 1.50, 1.75, 2.10, 2.63 +/- 2%
Perfusion Rod Travel Distance	10.5 cm (4.1 in)
Power	8 AA batteries (included)
Weight	13.6 kg (29.9 lbs)

Stereotactic Needle Biopsy Phantom

Enabling Critical Testing & Training



Highlights

- For use in localization accuracy test per ACR's stereotactic breast biopsy accreditation program
- Use upon system installation or repair, to ensure accurate needle placement
- Anthropomorphic shape allows accurate simulation of breast compression
- Re-usable - will not dry out, or leak when punctured; Masses can be biopsied multiple times
- 11 dense masses in three sizes; Two microcalcification clusters
- Compatible with standalone and add-on stereotactic biopsy systems

Specifications	
Dimensions	10 cm x 16.6 cm x 5 cm (6.5" x 2.5" x 4")
Phantom Weight	1.0 lb. (0.4 kg)
Phantom Volume	530 cc
Material	Polyurethane

Multi-Modality Breast Biopsy and Sonographic Trainer

A Versatile Tool for Shaping Best Practices




Highlights

- Designed to train users in aspects of breast imaging and image-guided interventional procedures - X-ray, Ultrasound, MRI
- Includes cystic and dense lesions embedded within breast background
 - Half of dense lesions spherical with embedded 100-300 micron microcalcification, half with spiculated shape
 - Calcifications serve as useful markers for image registration between modalities
- Features patent-pending Z-Skin™ membrane to simulate skin, providing protection from desiccation even after multiple sessions

Specifications	
Tray Dimensions	26 cm x 23 cm x 7.5 cm (10" x 9" x 3")
Breast Size	500 cc (14 cm x 11 cm at base, 8 cm high)
Total Weight	1 lb. (0.4 kg)
Membrane Material	Z-Skin™ elastomer
Background Material	Zerdine®, white
Cystic Masses	Qty: 5-10
Dense Masses	Material: Zerdine®

AAPM CT Performance Phantom

Meet AAPM Report #1 Guidelines



Highlights

- Comprehensive Testing: Measures ten CT performance parameters, aligning with AAPM Report #1 guidelines
- Versatile Design: Includes variable-size cavities for contrast tests and interchangeable inserts for dose measurements
- Precision Tools: Features inserts for assessing CT number linearity, resolution, and slice thickness
- Durable and Portable: Made from PMMA cast tubing, lightweight and easy to transport

See sunnuclear.com for specifications.

Image-Guided Abdominal Biopsy Phantom

Image-Guided Training and Demonstration



Highlights


- CT, MRI, and Ultrasound compatibility
- Simplified tool for abdominal biopsy, interventional training, and device demonstration
- Allows visual reference of needle placement
- Masses can be biopsied multiple times
- Improve performance of freehand abdominal biopsies
- Validate automated biopsy systems

See sunnuclear.com for specifications.

DBT QC Phantom

Thorough Tomosynthesis System

Performance Testing



Comprehensive Digital Testing

- Acceptance testing, daily and routine QC
- Tests image quality and stability of DBT systems
- Consistent, repeatable targets in homogeneous background
- Optional complex background provides clinically relevant challenge for target detection
- Slab configurations provide range of thicknesses with or without targets
- Developed to meet developing requirements of EUREF and AAPM TG-245

Specifications	
Overall Dimensions	127 mm x 80 mm x 100 mm
Individual Slab Dimensions	6 Slabs: 110 mm x 180 mm x 10 mm; 1 Slab: 115 mm x 180 mm x 10 mm (support slab); 1 Slab: 110 mm x 180 mm x 5 mm, semicircular shape
Phantom Weight	1.62 kg (3.55 lbs)
Materials	BR50/50, BRSW5050

Set Includes	4 Solid Homogeneous Slabs 1 cm thick; 1 Solid Homogeneous Slabs 0.5 cm thick; 3 Target Homogeneous Slabs 1 cm thick; 1 Positioning Holder with Magnetic Fixation
--------------	--

Mammo FFDM™ Phantom

Full Field Digital Mammography



Ensure Optimal FFDM Performance

- Evaluate artifacts over the entire detector with a single image
- Meet ACR, MSQA and EUREF requirements
- Test objects designed and located per ACR specifications, and reduced backscatter and equalized attenuation
- Meets ACR 2018 Digital Mammography Quality Control Manual requirements

Specifications	
Materials	Wax and acrylic equivalent to 4.2 cm thick compressed breast tissue
Nylon Fibers	6
Specks	6 Groups, Glass Spheres
Masses	6
Dimensions (L x W x H)	31.0 ± 0.1 x 19 ± 0.1 x 4.1 ± 0.03 cm
Dimensions: Wax Insert (L x W x H)	12.98 (+ 0, - 0.04) x 6.98 (+0, -0.04) x 0.7 ± 0.02 cm
CNR Cavity Depth	0.1 ± 0.005 cm
CNR Diameter	2.0 ± 0.05 cm
Compensator	9 mil Polyvinylidene Chloride
Case	Optional custom hard-sided case, with 1-year warranty

Mammo 156™ & 156D

Stereo™ Phantoms

Digital Mammography System QC,

Biopsy & Localization



Measure & Monitor Digital Mammography Systems

- Phantoms simulate the radiographic characteristics of compressed breast tissue
- Detect objects from 0.20 to 1.00 mm
- Monitor signal-to-noise, resolution and image quality
- Meet ACR and MSQA requirements
- Hang Mammo 156D on biopsy system detector during rotation

Specifications	
Materials	Wax and acrylic equivalent to 4.2 cm thick compressed breast tissue. 50% adipose & 50% glandular Mammo 156D fibers, specks and masses follow ACR specifications.
Nylon Fibers (Fibrils)	6 (156)
Nylon Fibers (monofilament) DIA (mm)	0.40, 0.54, 0.74, 0.93 (156D)
Micro-calcifications	5 Groups (156)
Micro-calcifications (Aluminum Oxide) DIA (mm)	0.20, 0.24, 0.32, 0.54 (156D)
Masses	5 (156)
Masses DIA (mm)	0.25, 0.50, 0.75, 1.00 (156D)
Dimensions (L x W x H)	10.2 x 10.8 x 4.5 cm (156) 6.7 x 6.8 x 6.1 cm (156D)
Case	Optional soft-sided case with foam insert, with 1-year warranty

Mammo 3D™

Performance Kit

Digital Mammography System QC



Acceptance Testing for 3D Tomosynthesis Systems

- Includes PMMA plates, spacers, aluminum plates and foils, steel plates and customized test tools
- Meet IEC Protocol 601223-3-6, EUREF/EFOMP 1.03 (Tomosynthesis), & German DIN 6868-14 requirements

Specifications	
Standard Test Plate	1 - 320 x 260 x 45 mm
10 mm PMMA Plate	7 - 320 x 260 x 10 mm
15 mm PMMA Plate	1 - 320 x 260 x 5 mm
2 mm PMMA Plates	7 - 40 x 20 x 2 mm
10 mm PMMA Spacers	2 - 180 x 15 x 10 mm
30 mm PMMA Spacers	2 - 180 x 30 x 30 mm
Geometric Distortion & Z-Resolution Phantom	1 - 320 x 260 x 5 mm
Custom Hard Case	Included
Aluminum Plates & Foils	
2 mm Aluminum Plate	1 - 100 x 100 x 2 mm
0.2 mm Aluminum Foil Sheet	1 - 10 x 10 x 0.2 mm
0.1 mm Aluminum Foil Sheets	8 - 100 x 100 x 0.1 mm

Steel Plates	
3 mm Stainless Steel Plate	1 - 320 x 260 x 3 mm
MTF Edge Tool	1 - 120 x 60 x 0.6 mm
Wire, Spacers, X-ray Rulers	
25 micron Tungsten Wire (cm)	100
Polystyrene Foam Spacers	5 - 240 x 180 x 20 mm
1 mm scale X-ray Rulers	4 - +2.5 to -5 cm


Mammo CESM™ Phantom

QC for Contrast Enhanced Spectral Mammography

Independently Verify Beam Qualities

- Stack of modules supports a variety of tests across a range of iodine concentrations and breast glandularity
- Blocks can be arranged to represent compressed breast for small to large patients

See sunnuclear.com for specifications.





Supporting Solutions

from the
broader Mirion
portfolio

As part of Mirion, Sun Nuclear is pleased to offer proven solutions from our Mirion Medical and Mirion Technologies product lines.

The following pages highlight Mirion innovations now available directly from your Sun Nuclear representative. These include our wireless dosimeter, a new radiation-tolerant camera, and a range of Health Physics offerings for effective radiation monitoring in healthcare environments.



Instadose®VUE

Wireless Dosimeter

Exposure Reporting and Feedback at Your Fingertips

- Configurable automatic, calendar-set dose read intervals programmed to the reporting schedule you select (weekly, monthly, quarterly, or custom)
- Perform on-demand dose reads anytime
- Access to current and historical exposure data online via any internet-enabled device
- Prompt risk mitigation through on-demand data access, enabling earlier intervention

Reduce Costs & Waste

- Employees keep their assigned dosimeters, eliminating the need to collect and redistribute dosimeters
- When staff changes occur, badges can be efficiently assigned or reassigned

See mirion.com for details and specifications.



evrCAM™ NEW

Radiation-Tolerant Pan-Tilt-Zoom Camera

Seamless Compatibility

- Designed for vaults using analog (Varian® Medical Systems) or digital (Elekta®) camera solutions
- Integrates with existing wiring, controllers, and camera viewing systems (Cat5e or equivalent cabling)
- Compatible with most video management systems (VMS)
- Mounts to wall or ceiling with a twist-lock design for fast, secure installation

Radiation Performance

- Withstands up to 200 Gy of cumulative exposure
- Maintains image quality with minimal image degradation up to 100 Gy*
- Shielded against neutron and photon radiation

Clarity & Control

- Visibility in low-light conditions
- Full pan-tilt zoom (PTZ)
- High-resolution color and black-and-white video with auto-detection stream

See sunnuclear.com for specifications.

Not available for sale in all markets

*Tested using 6 MV and 15 MV beam spectra



IC3™

NEW

Portable Ion Chamber Survey Meter

High Sensitivity for Staff & Patient Safety

- Highly stable, accurate dose measurement readings from 50 nanosecond X-Ray pulses
- Measures dose rate and accumulated dose
- Automated and wide measuring range of 1 μ Sv/hr to 1 Sv/hr (0.1 mR/hr to 100 R/hr)

Optimized User Experience

- Sealed electrometer provides protection in high humidity areas, no desiccant required
- Compact, lightweight and easy to use in one-hand operation
- Built-in memory with data storage to include routine measurement points, reducing workload and manual record-keeping
- Large color illuminated display for ease-of-use

See [sunnuclear.com](https://www.sunnuclear.com) for specifications.



RDS-Med™

Radiation Monitoring Area Monitor

Enhanced Radiation Safety in Medical Environments

- Provides immediate and clear alerts to maintain radiation safety standards
- Critical for protecting healthcare professionals and patients from ionizing radiation exposure

Modular and Configurable

- Designed for fixed installation in environments needing reliable, continuous radiation monitoring
- Transparent cover for easy viewing of internal and optional external probe measurements
- RDS-Med is easily removed for use as a hand-held survey meter, for shielding surveys and to identify local hot spots
- Modular signaling sets with visual and audible alarms (105 dBA siren) for clear and visual alerts of beam on or off

Robust & Reliable

- Designed for continuous operation with a 85-240 VAC power supply and backup internal batteries
- Offers area monitoring via LAN using WRM2™ data transmission protocol and web-based remote monitoring
- IP65 rated with protection caps, ensures durability and resistance to environmental factors
- Optional neutron and Beta modules are available

See [sunnuclear.com](https://www.sunnuclear.com) for mechanical and electrical characteristics.



DMC 3000™

Personal Electronic Dosimeter

Advanced Radiation Detection and Safety

- Precise, reliable detection of X-rays and gamma radiation for medical professionals in radiological environments
- Configurable alarms and alert settings for immediate notification when exposure exceeds user-defined thresholds


Durable & User-Friendly

- Compact, lightweight, and robust with a user-friendly interface and clear display for easy operation and readability
- Rugged, high-impact polycarbonate-ABS case that is easy to decontaminate and alcohol resistant
- Supports up to 12 months of battery life under typical use and up to 3000 hours in continuous mode
- Waterproof (IP67), shock, vibration, and drop resistant

Flexible and Versatile Use

- Can be used standalone in smaller clinics or integrated into a larger healthcare facility's ecosystem
- Compatible with additional modules for enhanced detection capacity and connectivity features, such as Bluetooth and neutron detection
- Supports incremental dose estimates from higher exposure procedures
- Optional neutron and beta modules are available

See [sunnuclear.com](https://www.sunnuclear.com) for mechanical, electrical and environmental characteristics.



ConnectStudio™

Connectivity Management Software

Stronger Exposure Monitoring and Supervision

- Visual displays of dose and rate supports radiation exposure reduction efforts
- Efficient and easy pairing with DMC 3000 with Bluetooth Module, and RDS-Med Survey Meter and Area Monitor
- Manages connections and reconnections automatically in case of lost signal

Operational Efficiency & Compatibility

- Operational telemetry supervision at a glance
- Facilitates quick actions in case of radiation alarms or pre-alarms
- Compatible with Windows 10 and Android systems, supporting a range of devices including PCs and tablets with integrated NFC reader



**Sun Nuclear
Headquarters (US)**

Phone
+1 (321) 259-6862

Address
3275 Suntree Blvd,
Melbourne, FL 32940

**Sun Nuclear
Virginia (US)**

Phone
+1 (757) 855-2765

Address
900 Asbury Ave
Norfolk, VA 23513

**Sun Nuclear
Germany**

Phone
T +49 6102 50495 00
F +49 6102 50495 29

Address
Landsberger Str. 318 80687
München, Germany

**SunServices™
Center - EMEA**

Phone
+31 20 399 90 41

Address
Verlengde Poolseweg 36
4818 CL Breda, The Netherlands



SUN NUCLEAR
A MIRION MEDICAL COMPANY

©2025 Mirion Technologies, Inc. or its affiliates. All rights reserved. Sun Nuclear, the Sun Nuclear logo, and other trade names of Sun Nuclear products listed herein are registered trademarks or trademarks of Mirion Technologies, Inc. or its affiliates in the United States and other countries. Third party trademarks mentioned are the property of their respective owners. All Rights Reserved. All data used is best available at time of publication. Data is subject to change without notice.

MKTG-4454 Sun Nuclear Product Solutions Brochure